

Keltron RF-VNCPC Rack Mount PC Provides Keltron RF7500 Access



Keltron RF-VNCPC Software

The following is a list of Keltron installed software used to provide Keltron RF7500 network access via Keltron router.

- UltraVNC remote desktop viewer preinstalled and preconfigured for on-site administration of Keltron RF7500 Radio Receivers
- Configured for secure remote access via UltraVNC server through the Keltron-provided router firewall so that dealers or system administrators may service the Keltron RF7500 receivers from off site
- Presets save time and effort when requesting Keltron's remote technical assistance for the Keltron RF7500 Radio Receivers
- Keltron RF7100 Configuration Wizard preinstalled for configuration of Keltron RF7100 Signal Converters
- Keltron RF7500 receiver system manuals and backups of configuration files included.

Features

- 19" 2U chassis
- Motherboard: FoxConn motherboard with Intel G41 chipset - supports 45nm processors with 1333MHz front side bus
- Processor: 2.6 GHz Intel Celeron Dual-Core CPU (800MHz FSB & 1MB L2 cache)
- Memory: 1GB DDR3 1333MHz system memory
- Hard drive: 500GB Western Digital 7200RPM SATA HDD
- LAN: onboard gigabit LAN
- Video: onboard Intel video
- Audio: onboard 5.1 channel HD audio
- Ports:
 - 6 x USB 2.0 ports (2 front, 4 rear)
 - 1 x RS232 serial port
 - 1 x LPT parallel port
- Power supply: 300W ATX12V power supply
- Operating system

Specifications

Case

- Construction: heavy-duty cold-rolled steel
- Drive capacity: exposed 1 x 5.25" and 1 x 3.5" drives
- Cooling: 1 8cm ball-bearing fan
- Front panel indicators: 1 x pwr on/off, 1 x HDD
- Front panel controls: 1 x pwr on/off, 1 x system reset
- Front panel connectors: 2 x USB
- Dimensions: 19" W x 19.6" L x 3.5" H
- Maximum expansion card length: 9.5"

Motherboard

- Processor:
 - Intel® Core™2 Quad, Core™2 Duo, Pentium® Dual-Core, Celeron Dual-Core, Celeron® processors, Socket T (LGA775)
 - Supports Intel® 45nm Multi-core processors
- Chipset: Intel® G41 + ICH7
- Memory: dual channel DDR3 800/667/533 x 2 DIMMs, max 4GB
- VGA on die: Intel® GMA 4500
- IDE: 1 x ATA 100
- Serial ATA(SATA)/RAID: 4 x SATAII
- Audio: 5.1 channel, Realtek®
- LAN: gigabit LAN, Realtek®
- Back panel I/O ports:
 - 1 x PS/2 keyboard port
 - 1 x PS/2 mouse port
 - 1 x serial port
 - 1 x parallel port
 - 1 x audio jack supports 3 jacks
 - 1 x VGA port
 - 4 x USB 2.0 ports
 - 1 x RJ45 LAN port

Keltron develops and manufactures universally-compatible, UL listed life safety event management systems for the municipal and proprietary markets. Solutions include Ethernet signaling systems, active network radio systems, distributed multiplex systems, digital communicator/receiver systems, and direct wire systems. This document is not intended for installation or maintenance purposes. All specifications are subject to changes without notice. For more information visit www.keltroncorp.com or contact us at 781-894-8710.

© 2011 Keltron Corporation. All rights reserved.